PREMIERWALL EXPLORE

52"-54" Fabric-Backed Contract Wallcovering

PHYSICAL PROPERTIES

Roll Size 52"-54" x 30yds **Weight** 20/21 oz PLY

Backing Woven / Non-woven

Meets or exceeds Federal Specification CCC-W-408A physical characteristics for Type II Wallcovering

FIRE SAFETY

- Class "A" Fire rated
- NFPA255 (UL723, CAN \$102M) Tunnel Test1
- NFPA 286 Corner Burn Test2
- Meets requirements for Flame Spread, Smoke Developed and Flashover
- UL Labelled and Listed

CLEANING/MAINTENANCE

Metallic finishes can be discolored with the use of caustic cleaners. Thus, we recommend only the use of a mild soap solution for cleaning these products. If stronger cleaning is required, first evaluate the cleaner in an inconspicuous location.

ANTI-MICROBIAL FEATURES

PREMIERWALL EXPLORE contain mildew and staph resistant additives in the vinyl and plastisol. This provides the wallcovering with resistance to the growth of mildew and bacteria, including mold, fungi, pink stain and black fungal stain.

BATCHING

Since slight variations in shading may occur from time to time, it is important that the roll carrying the same batch number be used in any one area.

ORIGIN

USA